



REFLOW CLEANER 88

A water-based cleaning fluid designed for soldering device manual cleaning - for high contamination.

Ready-mix designed for direct use

Designed for cleaning of most soldering paste and flux types

Developed for areas with strong contamination levels, increased smell, and lower compatibility with aluminum-based alloys.

Recommended areas for use

Recommended cleaning technology

1. Reflow ovens - flux residues

manual cleaning

2. Soldering waves - flux residues

manual cleaning

3. Other operating contaminants - dust, grease, etc

manual cleaning

Process table

Cleaning technology	Cleaning	1. rinse	2. rinse	Drying
Manuel cleaning	Reflow Cleaner 88	-	-	with wiper

Informace o produktu

- Designed for all types of soldering devices, fluxers and other production technologies.
- High effectiveness while preserving compatibility with low smell aluminum-based alloys
- A special sprayer creates „active foam“, which remains active on vertical parts of machines for a longer time
- Environmentally friendly - biodegradable
- Does not contain tensides, no risk of solid residue occurrence on the cleaned part surfaces
- No inflammation point, can be applied to hot surfaces



Table of physical and chemical properties

Product appearance:	clear liquid
Odour, aroma:	slightly ethereal
pH:	10 - 11
VOC content:	25%
Recommended process temperature:	ambient temperature
Ignition temperature:	inflammable
Flash point:	inflammable
Density at 20°C:	0,98 kg/l



Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at www.dct.cleaning



Date of issue:
1.11.2015

Detailed information can be found in the Safety Data Sheet of **Reflow Cleaner 88**.



REFLOW CLEANER 88



Packing

bottle: 1 litre; can: 5, 10, 25 litres



Transport

Product is not hazardous for transport.



Handling

Turn the manual sprayer nozzle from position STOP to 90° before the first use. Then apply a necessary amount to the part to be cleaned, wait for several minutes and wipe residues using a smooth piece of cloth. Repeat the procedure, if necessary.



Storage

Should be stored in closed containers, in ventilated areas at the temperature from 5 to 25°C.



Best before

The maximum usable life for this product is 24 months from the production date.



RoHS
Compliant



REACH
SVHC



BIODEGRADABLE



Date of issue:
1.11.2015

Detailed information can be found in the
Safety Data Sheet of **Reflow Cleaner 88**.