

HYDRAULIC TESTER

Service Accessories

Fittings/Adapters For the 200
GPM Hydraulic Tester

ATTACH TO THE HT200 HYDRAULIC TESTER BY THE USE OF FLANGED-HEAD ADAPTERS AND SPLIT FLANGES, OR BY A SET OF FEMALE SOTRAIGHT ADAPTERS.

FLANGED HEAD ADAPTER UNIONS AND SPLIT FLANGE KIT


No. 203154 – Straight flange adapter. 1½" flanged-head to 1½" NPSM female swivel. Wt., 2.2 lbs.

No. 203155 – 45° flange adapter. 1½" flanged-head by 1½" NPSM female swivel. Wt., 3.2 lbs.

No. 203156 – 90° flange adapter. 1½" flanged-head by 1½" NPSM female swivel. Wt., 4.2 lbs.

No. 203017 – Split flange kit. Consists of four flange halves and attaching bolts to permit use of 1½"








I.D. flange adapters listed at left. Wt., 2.9 lbs.



FEMALE STRAIGHT FLANGE ADAPTER

No. 203003 – Consists of two female straight flange adapters with attaching bolts. When attached to inlet/outlet ports, allows connection of 1½" NPT male hose ends to tester. Wt., 8.5 lbs.

HYDRAULIC FITTINGS FOR USE WITH ALL TESTERS.

	No. 16954 – 90° swivel adapter, ¾" NPTF male x ¾" NPSM female. Wt., 0.8 lb.		No. 26073 – Swivel adapter, ¾" NPTF female x ½" NPSM female. Wt., 0.3 lb.
	No. 22041 – Coupler, ¾" NPTF male x ¾"-16 female ORB. Wt., 0.5 lb.		No. 26074 – 45° swivel adapter, ¾" NPSM female x ¾" NPTF male. Wt., 0.6 lb.
	No. 22042 – Coupler, ¾" –16 female ORB x 1½"-12 female 37° JIC. Wt., 0.4 lb.		No. 26075 – Swivel adapter, ¾" NPSM female x ¾" NPTF female. Wt., 0.4 lb.
	No. 22043 – Coupler, ¾" –16 female ORB x 9/16"-18 female 37° JIC. Wt., 0.4 lb.		No. 26076 – Swivel adapter, ¾" NPTF male x ¾" NPSM female. Wt., 0.4 lb.
	No. 22044 – Coupler, ¾" –16 female ORB x ½"-20 female 37° JIC. Wt., 0.4 lb.		No. 26077 – Cap, ¾" NPTF. Wt., 0.6 lb.
	No. 27737 – Swivel adapter, ¾" –16 male x ¾" NPSM female. For use with No. 9785 hose, which has ¾" NPTF male thread. Wt., 0.3 lb.		No. 26078 – Plug, ¾" NPTF. Wt., 0.3 lb.
	No. 27287 – Coupler, ¾" –16 UNF female ORB x 7/8"-14 UNF female 37° JIC. Wt., 0.4 lb.		No. 26079 – Adapter, ¾" NPTF female x 1½"-12 male ORB. Wt., 0.4 lb.
	No. 13449 – Cap, 1½"-12 UNF female, ¾" O.D. tube, 37° flare. Wt., 0.2 lb.		No. 208402 – 45° union adapter, 7/8"-14 UNF male 37° JIC x ¾" NPTF female. 3,000 psi working pressure. Wt., 0.6 lb.
	No. 26068 – 45° swivel adapter, 1" NPTF male x ¾" NPSM female. Wt., 0.8 lb.		No. 208401 – 45° union adapter, 7/8"-14 UNF male 37° JIC x ¾" NPTF female. Wt., 0.7 lb.
	No. 26069 – Swivel adapter, 1" NPTF female x ¾" NPSM female. Wt., 0.5 lb.		No. 206753 – Coupler, 1½"-12 UNF female 37° JIC x ¾" NPTF female. Wt., 1.1 lbs.
	No. 26070 – Adapter, 1" NPTF male x ¾" NPTF female. Wt., 0.3 lb.		No. 26666 – Connector, 1½"-12 UNF male 37° JIC x ¾" NPTF male. Wt., 0.4 lb.
	No. 26071 – Service tee, ¾" NPTF female (2) x ¾" NPTF male. Wt., 0.9 lb.		No. 28984 – Straight adapter, ¾" NPTF female x 1½"-12 UN male 37° JIC. Wt., 0.6 lb.
	No. 26072 – Swivel adapter, ¾" NPSM female x ½" NPTF male. Wt., 0.4 lb.		No. 28985 – Straight adapter union, 1½"-12 UN female 37° JIC x ¾" NPTF female. Wt., 1.3 lbs.

NOTE: The recommended maximum working pressure on the above fittings is 5,000 psi except the 208402.

